


TURCK M8 picofast® Connectivity

3-Wire Cordsets, Snap Lock (Locking Sleeve)

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 125 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>PKG ..Z**</p>	<p>PKG 3Z-* PKW 3Z-*</p>	<p>PSG 3-* PSW 3-*</p>	<p>AWM, PVC Yellow, 3x24 AWG, 105°C, 4.4 mm OD, Cable #RF50642-*M†, flexlife®</p>	<p>Female</p> <p>Male</p>
<p>PKW ..Z**</p>	<p>PKG 3Z-*/S90 PKW 3Z-*/S90</p>	<p>PSG 3-*/S90 PSW 3-*/S90</p>	<p>AWM, TPU Black, 3x24 AWG, 90°C, 4.4 mm OD, Cable #RF50587-*M†, Cut/Abrasion Immune</p>	
<p>PSG ..</p>	<p>PKG 3Z-*/S90/S618 PKW 3Z-*/S90/S618</p>	<p>PSG 3-*/S90/S618 PSW 3-*/S90/S618</p>	<p>AWM, TPU Black, 3x24 AWG, 90°C, 4.5 mm OD, Cable #RF51166-*M†, Cut/Abrasion Immune, flexlife-20, High Flex - Over 20 Million Cycles</p>	
<p>PSW ..</p>	<p>PKG 3Z-*/XOR PKW 3Z-*/XOR</p>	<p>PSG 3-*/XOR PSW 3-*/XOR</p>	<p>AWM, TPU Black, 3x24 AWG, 90°C, 4.4 mm OD, Cable #RF50601-*M†, Cut/Abrasion Immune, EMI/RFI Protection</p>	
	<p>PKG 3Z-*/S90/S618 PKW 3Z-*/S90/S618</p>	<p>PSG 3-*/S90/S618 PSW 3-*/S90/S618</p>	<p>AWM, TPU Black, 3x24 AWG, 90°C, 4.4 mm OD, Cable #RF50601-*M†, Cut/Abrasion Immune, EMI/RFI Protection</p>	
	<p>PKG 3Z-*/XOR PKW 3Z-*/XOR</p>	<p>PSG 3-*/XOR PSW 3-*/XOR</p>	<p>PVC Orange, 3x24 AWG, 80°C, 250°C short term, 4.4 mm OD, Cable #RF04449-*M†, Weld Flash Immune, High Temp. Immune</p>	
	<p>PKG 3Z-*/S760 PKW 3Z-*/S760</p>	<p>PSG 3-*/S760 PSW 3-*/S760</p>	<p>AWM, PVC Black, 3x24 AWG, 105°C, 4.4 mm OD, Cable #RF50585-M†, flexlife</p>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Locking sleeve material is POM.. "PKG..Z".

† See Section N for **reelfast**® cable information.