


- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance Grade B
- Temperature Range -200 to 600 Degrees C
- 1/4 Inch Diameter 316 Stainless Steel Sheath
- 3 Wire
- Sheath Length: 18 Inches
- One-Time Adjustable Compression Fitting - 316 Stainless Steel - 1/4 Inch NPT
- Extension Leadwire Transition with Relief Spring 400 Degrees F
- Leadwire - Fiberglass Insulation - Stranded Conductor - Stainless Steel Overbraid
- Extension Wire B Length: 240 Inches
- 2 Inch Split Leads 1/4 Inch Stripped



CATALOG #: R1T185H483-018-05B-15-F3B240-2

TAGGING:

STAMPING:

		FOR: PYROMATION	
		TITLE: RTD ASSEMBLY	
TOLERANCES		SIZE: A	DWG. NO. & SHEET NO: 10001013188 REV.
FRACTION DIM =		DRAWN BY: RT01	DATE: 09/21/2020
DECIMAL DIM .XX =		 pyromation [®] beyond measure FORT WAYNE, INDIANA 260-484-2580	
DECIMAL DIM .XXX =			
ANGULAR DIM =			
This document is PROPRIETARY to Pyromation, Inc.			