


- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance Grade B
- Temperature Range -200 to 600 Degrees C
- 3/8 Inch Diameter 316 Stainless Steel Sheath
- 3 Wire
- Sheath Length: 6 Inches
- One-Time Adjustable Compression Fitting - 316 Stainless Steel - 1/4 Inch NPT
- Extension Leadwire Transition with Relief Spring 400 Degrees F
- Leadwire - Fluoropolymer Insulation - Stranded Conductor
- Extension Wire B Length: 240 Inches
- 2 Inch Split Leads 1/4 Inch Stripped

TAGGING:

STAMPING:



CATALOG #: R1T185H683-006-05B-15-T3240-2

		FOR: PYROMATION	
		TITLE: RTD ASSEMBLY	
TOLERANCES		SIZE: <b>A</b>	DWG. NO. & SHEET NO: <b>10001013269</b> REV.
FRACTION DIM =		DRAWN BY: RT01	DATE: 09/23/2020
DECIMAL DIM .XX =			
DECIMAL DIM .XXX =			
ANGULAR DIM =			
This document is PROPRIETARY to Pyromation, Inc.		FORT WAYNE, INDIANA 260-484-2580	