

2-Wire Cordsets, Standard Plug Body

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout	
RK ..** 1.673 [42.5] Ø.571 [14.5] M12x1 WK ..** 1.280 [32.5] .984 [25.0] Ø.591 [15.0] M12x1 RS ..** 1.546 [39.3] Ø.571 [14.5] M12x1 WS ..** 1.264 [32.1] 1.220 [31.0] Ø.531 [13.5] M12x1	RK 4.2T-* WK 4.2T-*	RS 4.2T-* WS 4.2T-*	AWM PVC Grey, 2x20 AWG, 105°C, 5.1 mm OD, Cable #RF50529-*M†, flexlife®	1. N/C 2. N/C 3. BN 4. BU	Female
	RK 4.2T-*/S90 WK 4.2T-*/S90	RS 4.2T-*/S90 WS 4.2T-*/S90	AWM TPU Grey, 2x20 AWG, 90°C, 4.8 mm OD, Cable #RF50772-*M†, Cut/Abrasion Immune, tray rated		
	RK 4.2T-*/S748 WK 4.2T-*/S748	RS 4.2T-*/S748 WS 4.2T-*/S748	AWM PVC Yellow, 2x22 AWG, 105°C, 5.1 mm OD, Cable #RF50650-*M†, flexlife	1. WH 2. N/C 3. N/C 4. BK	
	RK 4.21T-*/S1511 WK 4.21T-*/S1511	RS 4.21T-*/S1511 WS 4.21T-*/S1511	AWM PVC Grey, 2x20 AWM PVC, 105°C, 5.1 mm OD, Cable #RF50529-*M†		
	RK 4.21T-* WK 4.21T-*	RS 4.21T-* WS 4.21T-*	AWM PVC NAMUR Blue, 2x20 AWG, 105°C, 5.1 mm OD, Cable #RF20003-*M†	1. BN 2. BU 3. N/C 4. N/C	Male
	RK 4.21T-*/S90 WK 4.21T-*/S90	RS 4.21T-*/S90 WS 4.21T-*/S90	AWM TPU NAMUR Blue, 2x20 AWG, 90°C, 5.1 mm OD, Cable #RF50657-*M†, Cut/Abrasion Immune		
	RK 4.22T-* WK 4.22T-*	RS 4.22T-* WS 4.22T-*	AWM PVC Grey, 2x20 AWG, 105°C, 5.1 mm OD, Cable #RF50529-*M†, flexlife	1. BN 2. N/C 3. BU 4. N/C	
	RK 4.23T-* WK 4.23T-*	RS 4.23T-* WS 4.23T-*		1. BN 2. N/C 3. N/C 4. BU	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RK .."; "RKK .." indicates nylon and "RKV .." indicates stainless steel.

† See Section N for **reelfast**® cable information.