


5-Wire Cordsets, Standard

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 9 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
RKM ..** WKM ..** RSM ..** WSM ..**	RKM 50-*M WKM 50-*M RKM 50-*M/S90 WKM 50-*M/S90 RKM 50-*M/S101 WKM 50-*M/S101 RKM 50-*M/S1551 WKM 50-*M/S1551 RKM 511-*M WKM 511-*M RKM 511-*M/S600 WKM 511-*M/S600	RSM 50-*M WSM 50-*M RSM 50-*M/S90 WSM 50-*M/S90 RSM 50-*M/S101 WSM 50-*M/S101 RSM 50-*M/S1551 WSM 50-*M/S1551 RSM 511-*M WSM 511-*M RSM 511-*M/S600 WSM 511-*M/S600	ITC PVC Yellow, 5x18 AWG, 105°C, 7.6 mm OD, Cable #RF50549-*M†, flexlife®, 600V AWM TPU Yellow, 5x18 AWG, 90°C, 7.2 mm OD, Cable #RF50751-*M†, Cut/Abrasion Immune, 600V AWM TPE Yellow, 5x18 AWG, 105°C, 7.2 mm OD, Cable #RF51174-*M†, flexlife-20, high flex over 20 million cycles, 600V ITC PVC Yellow, 5x18 AWG, 105°C, 7.6 mm OD, Cable #RF50578-*M†, Yellow conductor instead of Green/Yellow, 600V ITC PVC Yellow, 5x18 AWG, 105°C, 7.6 mm OD, Cable #RF50521-*M†, flexlife, 600V SJOOW CPE Yellow, 5x18 AWG, 105°C, 9.4 mm OD, Cable #RF50659-*M†, Weld Flash Immune, Flame Immune, 300V	1. BK 2. BU 3. GN/YE 4. BN 5. WH 1. BK 2. BU 3. YE 4. BN 5. WH 1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK Female Male

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon, "RKV .." indicates stainless steel, and "RKVH .." indicates stainless steel hex.

† See Section N for **reelfast**® cable information.