

9 and 10-Wire *minifast*® Cordsets, "C" Style Heavy Duty

- Straight Male Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 600 VAC/DC, 7 A



Housing Style	Part Number	Cable	Features		Pinout		
	RSM 96-*M	ITC PLTC PVC Yellow 9x16 AWG 105°C 12.5 mm OD Cable #RF51033-*M <sup>†</sup>	<i>flexlife</i> ®	<ol style="list-style-type: none"> <li>OG</li> <li>BU</li> <li>RD/BK</li> <li>GN/BK</li> <li>WH</li> <li>RD</li> <li>GN</li> <li>WH/BK</li> <li>BK</li> </ol>			
	RSM 96-*M/S90	ITC PLTC PURYellow 9x16 AWG 105°C 12.5 mm OD Cable #RF51140-*M <sup>†</sup>	<i>Cut/abrasion Immune</i>				
	RSM 96-*M/S101	AWM TPE Yellow 9x16 AWG 105°C 10.5 mm OD Cable #RF51051-*M <sup>†</sup>	<i>flexlife-10, High flex - over 10 million cycles</i>				
	RSM 96-*M/S600	SOOW CPE Yellow 9x16 AWG 105°C 15.2 mm OD Cable #RF51021-*M <sup>†</sup>	<i>Weld Flash Immune, Flame Immune</i>				
	RSM 96-*M/S1587	AWM TPE Yellow 9x16 AWG 105°C 11.2 mm OD Cable #RF51013-*M <sup>†</sup>	<i>weldlife, Weld flash Immune</i>				
	RSM 106-*M	ITC PLTC PVC Yellow 10x16 AWG 105°C 12.5 mm OD Cable #RF51034-*M <sup>†</sup>	<i>flexlife</i>			<ol style="list-style-type: none"> <li>OG</li> <li>BU</li> <li>WH/BK</li> <li>RD/BK</li> <li>GN/BK</li> <li>OG/BK</li> <li>RD</li> <li>GN</li> <li>BK</li> <li>WH</li> </ol>	
	RSM 106-*M/S90	ITC/PLTC Yellow 10x16 AWG 105°C 12.5 mm OD Cable #RF51141-*M <sup>†</sup>	<i>Cut/abrasion Immune</i>				
	RSM 106-*M/S101	AWM TPE Yellow 10x16 AWG 105°C 10.5 mm OD Cable #RF51052-*M <sup>†</sup>	<i>flexlife-10, High flex - over 10 million cycles</i>				
	RSM 106-*M/S600	SOOW CPE Yellow 10x16 AWG 105°C 15.7 mm OD Cable #RF51022-*M <sup>†</sup>	<i>Weld Flash Immune, Flame Immune</i>				
	RSM 106-*M/S1587	AWM TPE Yellow 10x16 AWG 105°C 12.5 mm OD Cable #RF51015-*M <sup>†</sup>	<i>weldlife, Weld flash Immune</i>				

\* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

Standard coupling nut material is nickel plated brass "RSM .."; "RSV .." indicates 316 stainless steel.

<sup>†</sup> See Section N for *reelfast*® cable information.

9 and 10-Wire *minifast*® Cordsets, "C" Style Heavy Duty

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 600 VAC/DC, 7 A



Housing Style	Part Number	Cable	Features		Pinout
	WKM 96-*M	ITC PLTC PVC Yellow 9x16 AWG 105°C 12.5 mm OD Cable #RF51033-*M <sup>†</sup>	<i>flexlife</i> ®	1. OG 2. BU 3. RD/BK 4. GN/BK 5. WH 6. RD 7. GN 8. WH/BK 9. BK	
	WKM 96-*M/S90	ITC PLTC PUR Yellow 9x16 AWG 105°C 12.5 mm OD Cable #RF51140-*M <sup>†</sup>	<i>Cut/abrasion Immune</i>		
	WKM 96-*M/S101	AWM TPE Yellow 9x16 AWG 105°C 10.5 mm OD Cable #RF51051-*M <sup>†</sup>	<i>flexlife-10, High flex - over 10 million cycles</i>		
	WKM 96-*M/S600	SOOW CPE Yellow 9x16 AWG 105°C 15.2 mm OD Cable #RF51021-*M <sup>†</sup>	<i>Weld Flash Immune, Flame Immune</i>		
	WKM 96-*M/S1587	AWM TPE Yellow 9x16 AWG 105°C 11.2 mm OD Cable #RF51013-*M <sup>†</sup>	<i>weldlife, Weld flash Immune</i>		
	WKM 106-*M	ITC PLTC PVC Yellow 10x16 AWG 105°C 12.5 mm OD Cable #RF51034-*M <sup>†</sup>	<i>flexlife</i>		
WKM 106-*M/S90	ITC/PLTC Yellow 10x16 AWG 105°C 12.5 mm OD Cable #RF51141-*M <sup>†</sup>	<i>Cut/abrasion Immune</i>			
WKM 106-*M/S101	AWM TPE Yellow 10x16 AWG 105°C 10.5 mm OD Cable #RF51052-*M <sup>†</sup>	<i>flexlife-10, High flex - over 10 million cycles</i>			
WKM 106-*M/S600	SOOW CPE Yellow 10x16 AWG 105°C 15.7 mm OD Cable #RF51022-*M <sup>†</sup>	<i>Weld Flash Immune, Flame Immune</i>			
WKM 106-*M/S1587	AWM TPE Yellow 10x16 AWG 105°C 12.5 mm OD Cable #RF51015-*M <sup>†</sup>	<i>weldlife, Weld flash Immune</i>			

\* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

Standard coupling nut material is nickel plated brass "WKM .."; "WKV .." indicates 316 stainless steel.

<sup>†</sup> See Section N for *reelfast*® cable information.