



CATALOG #: R1T185L483-S4C0408-SC-8HN31

TAGGING:

STAMPING:

- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance Grade B
- Temperature Range -200 to 200 Degrees C
- 1/4 Inch Diameter 316 Stainless Steel Sheath
- 3 wire
- Thermowell: Standard Duty Threaded (NPT) - 0.260 Bore
- 316 Stainless Steel
- 1/2 Inch NPT Pipe Size
- S Dimension: 4 Inches
- U Dimension: 2(1/2) Inches
- Self-contained Spring-loaded Element
- 1/2 Inch x 1/2 Inch NPT Stainless Steel Hex Nipple
- Aluminum Screw Cover Head - NEMA 4X Rated

		FOR: PYROMATION	
		TITLE: SPRING LOADED SENSOR ASSEMBLY	
		SIZE: B	DWG. NO. & SHEET NO: 10001017420
		REV.	
TOLERANCES		DRAWN BY: GP03	DATE: 03/30/2021
FRACTION DIM =			
DECIMAL DIM .XX =			
DECIMAL DIM .XXX =			
ANGULAR DIM =		<p>This document is PROPRIETARY to Pyromation, Inc.</p>	