

3-Wire Cordsets, Standard Duty

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout	
KB ..** 1.614 [41.0] Ø.551 [14.0] 1/2-20UNF WKB ..** 1.256 [31.9] .945 [24.0] Ø.551 [14.0] 1/2-20UNF SB ..** 1.536 [39.0] Ø.571 [14.5] 1/2-20UNF WSB ..** 1.256 [31.9] 1.220 [31.0] Ø.551 [14.0] 1/2-20UNF	KB 3T-* WKB 3T-*	SB 3T-* WSB 3T-*	AWM PVC Yellow, 3x22 AWG, 105°C, 5.1 mm OD, Cable #RF50531-*M†	1. GN 2. RD/BK 3. RD/WH	Female
	KB 3T-*/S90 WKB 3T-*/S90	SB 3T-*/S90 WSB 3T-*/S90	AWM TPU Yellow, 3x18 AWG, 90°C, 5.7 mm OD, Cable #RF50547-*M†, Cut/Abrasion Immune		
	KB 3T-*/S105 WKB 3T-*/S105	SB 3T-*/S105 WSB 3T-*/S105	AWM PVC Yellow, 3x22 AWG, 105°C, 5.7 mm OD, Cable #RF50535-*M†, Braided Shield		
	KB 3T-*/S749 WKB 3T-*/S749	SB 3T-*/S749 WSB 3T-*/S749	AWM PVC Yellow, 2x22 AWG, 105°C, 5.1 mm OD, Cable #RF50650-*M†, 3-pin with 2 conductors	1. N/C 2. BK 3. WH	Male
	KB 3T-*/S1507 WKB 3T-*/S1507	SB 3T-*/S1507 WSB 3T-*/S1507	AWM TPE Grey, 3x20 AWG 105°C, 5.7 mm OD, Cable #RF50940-*M†, Flexlife-20, High Flex - Over 20 million cycles	1. BK 2. BN 3. BU	
	KB 3T-*/XOR WKB 3T-*/XOR	SB 3T-*/XOR WSB 3T-*/XOR	AWM PVC Yellow, 3x18 AWG, 80°C, 250°C short term, 5.7 mm OD, Cable #RF04159-*M†, Weld Flash Immune, High Temp Immune	1. GN 2. RD 3. RD/WH	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "KB .."; "KKB .." indicates nylon and "KBV .." indicates stainless steel.

† See Section N for **reelfast**® cable information.