

# TURCK 7/8" minifast® Connectivity Products



## 5 and 6-Wire Cordsets, Heavy Duty

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 600 V, 10 A (5-pin), 8 A (6-pin)



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>RKM ..**</b></p>	RKM 55-*M WKM 55-*M	RSM 55-*M WSM 55-*M	STOW PVC Yellow, 5x16 AWG, 105°C, 13.2 mm OD, Cable #RF50540-*M†, flexlife*	1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK
<p><b>WKM ..**</b></p>	RKM 55-*M/S600 WKM 55-*M/S600	RSM 55-*M/S600 WSM 55-*M/S600	SOOW CPE Yellow, 5x16 AWG, 105°C, 13 mm OD, Cable #RF50597-*M†, Weld Flash Immune, Flame Immune	1. RD 2. RD 3. GN 4. RD 5. RD
<p><b>RKM 56-*M</b> <b>WKM 56-*M</b></p>	RKM 56-*M WKM 56-*M	RSM 56-*M WSM 56-*M	SEOW/STOW PVC Yellow, 5x16 AWG, 105°C, 13.2 mm OD, Cable #RF50539-*M†, flexlife	1. WH 2. RD 3. GN 4. OG 5. BK
<p><b>RSM ..**</b></p>	RKM 56-*M/S1587 WKM 56-*M/S1587	RSM 56-*M/S1587 WSM 56-*M/S1587	SEOW/STOW TPE Yellow, 5x16 AWG, 105°C, 13.2 mm OD Cable #RF51265-*M†, weldlife, Weld Flash Immune	1. WH 2. RD 3. GN 4. OG 5. BK
<p><b>WSM ..**</b></p>	RKM 66-*M WKM 66-*M	RSM 66-*M WSM 66-*M	STOW PVC Yellow, 6x16 AWG, 105°C, 13.7 mm OD, Cable #RF50565-*M†, flexlife	1. WH 2. RD 3. GN 4. OG 5. BK 6. BU
<p><b>RKM 66-*M/S1587</b> <b>WKM 66-*M/S1587</b></p>	RKM 66-*M/S1587 WKM 66-*M/S1587	RSM 66-*M/S1587 WSM 66-*M/S1587	SEOW/STOW TPE Yellow, 6x16 AWG, 105°C, 13.7 mm OD, Cable #RF51564-*M†, weldlife, Weld Flash Immune	1. WH 2. RD 3. GN 4. OG 5. BK 6. BU

Cordsets

\* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon, "RKY .." indicates stainless steel, and "RKVH .." indicates stainless steel hex.  
 † See Section N for **reelfast**® cable information.