

## 4, 5 and 6-Wire Cordsets, Standard Duty

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



| Connector Style                              | Female Part Number            | Male Part Number              | Features                                                                                                            | Pinout                                  |
|----------------------------------------------|-------------------------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| <p><b>KB ..**</b></p> <p><b>WKB ..**</b></p> | KB 4T-*<br>WKB 4T-*           | SB 4T-*<br>WSB 4T-*           | AWM PVC Yellow, 4x22 AWG, 105°C, 5.7 mm OD, Cable #RF50555-*M† flexlife®, UL Listed, CSA Recognized                 | <p><b>Female</b></p> <p><b>Male</b></p> |
|                                              | KB 4T-*/S90<br>WKB 4T-*/S90   | SB 4T-*/S90<br>WSB 4T-*/S90   | AWM TPU Yellow, 4x22 AWG, 105°C, 5.7 mm OD, Cable #RF50614-*M† Cut/Abrasion Immune, UL Listed, CSA Recognized       |                                         |
|                                              | KB 4T-*/S105<br>WKB 4T-*/S105 | SB 4T-*/S105<br>WSB 4T-*/S105 | AWM PVC Yellow, 4x22 AWG, 105°C, 5.7 mm OD, Cable #RF50656-*M† Braided Copper Shield, UL Listed, CSA Recognized     |                                         |
|                                              | KB 4T-*/S727<br>WKB 4T-*/S727 | SB 4T-*/S727<br>WSB 4T-*/S727 | AWM TPU Grey, 4x22 AWG, 90°C, 5.1 mm OD, Cable #RF50532-*M† Special Conductor Color Code, UL Listed, CSA Recognized |                                         |
| <p><b>SB ..**</b></p> <p><b>WSB ..**</b></p> | KB 5T-*<br>WKB 5T-*           | SB 5T-*<br>WSB 5T-*           | AWM PVC Yellow, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50556-*M† flexlife®, UL Listed, CSA Recognized                 | <p><b>Female</b></p> <p><b>Male</b></p> |
|                                              | KB 6T-*<br>WKB 6T-*           | SB 6T-*<br>WSB 6T-*           | AWM PVC Yellow, 6x22 AWG, 105°C, 6.2 mm OD, Cable #RF51003-*M† flexlife                                             |                                         |

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "KB .."; "KKB .." indicates nylon and "KBV .." indicates stainless steel.

† See Section N for **reelfast**® cable information.