


TURCK 7/8" minifast® Connectivity Products



5-Wire Cordsets, Standard

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 9 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>RKM ..**</p>	RKM 50-*M WKM 50-*M	RSM 50-*M WSM 50-*M	ITC PVC Yellow, 5x18 AWG, 105°C, 7.6 mm OD, Cable #RF50549-*M†, flexlife®, 600V	<p>Female</p> <p>Male</p>
<p>WKM ..**</p>	RKM 50-*M/S90 WKM 50-*M/S90	RSM 50-*M/S90 WSM 50-*M/S90	AWM TPU Yellow, 5x18 AWG, 90°C, 7.2 mm OD, Cable #RF50751-*M†, Cut/Abrasion Immune, 600V	
<p>RSM ..**</p>	RKM 50-*M/S101 WKM 50-*M/S101	RSM 50-*M/S101 WSM 50-*M/S101	AWM TPE Yellow, 5x18 AWG, 105°C, 7.2 mm OD, Cable #RF51174-*M†, flexlife-20, high flex over 20 million cycles, 600V	
<p>RSM ..**</p>	RKM 50-*M/S1551 WKM 50-*M/S1551	RSM 50-*M/S1551 WSM 50-*M/S1551	ITC PVC Yellow, 5x18 AWG, 105°C, 7.6 mm OD, Cable #RF50578-*M†, Yellow conductor instead of Green/Yellow, 600V	
<p>WSM ..**</p>	RKM 511-*M WKM 511-*M	RSM 511-*M WSM 511-*M	ITC PVC Yellow, 5x18 AWG, 105°C, 7.6 mm OD, Cable #RF50521-*M†, flexlife, 600V	
<p>WSM ..**</p>	RKM 511-*M/S600 WKM 511-*M/S600	RSM 511-*M/S600 WSM 511-*M/S600	SJOOW CPE Yellow, 5x18 AWG, 105°C, 9.4 mm OD, Cable #RF50659-*M†, Weld Flash Immune, Flame Immune, 300V	

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon, "RKV .." indicates stainless steel, and "RKVH .." indicates stainless steel hex.
 † See Section N for reelfast® cable information.