



TAGGING:

- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance (1/5) Class B
- Temperature Range -30 to 150 Degrees C
- 1/4 Inch Diameter 316 Stainless Steel Sheath
- 3 Wire
- Standard Duty Threaded (NPT) - 0.260 Bore
- 316 Stainless Steel
- 1/2 Inch NPT Pipe Size
- S Dimension: 6(1/2) Inches
- U Dimension: 5 Inches
- Spring-loaded Element
- 1/2 Inch x 1/2 Inch NPT Stainless Steel Hex Nipple
- 316 L Stainless Steel Screw Cover Head - NEMA 4X Rated

STAMPING:

CATALOG #: R5T185L483-S4C06(1/2)08-SL-8HN91

		FOR: PYROMATION	
		TITLE: SPRING LOADED SENSOR ASSEMBLY	
		SIZE: B	DWG. NO. & SHEET NO: 10386000236
		REV.	
TOLERANCES		DRAWN BY: GP03	DATE: 1/25/2023
FRACTION DIM =			
DECIMAL DIM .XX =			
DECIMAL DIM .XXX =			
ANGULAR DIM =		<p>This document is PROPRIETARY to Pyromation, Inc.</p>	