



TAGGING:

STAMPING:

- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance (1/5) Class B
- Temperature Range -30 to 150 Degrees C
- 1/4 Inch Diameter 316 Stainless Steel Sheath
- 3 Wire
- Standard Duty Threaded (NPT) - 0.260 Bore
- 316 Stainless Steel
- 1/2 Inch NPT Pipe Size
- S Dimension: 3 Inches
- U Dimension: 1(1/2) Inches
- Self-contained Spring-loaded Element
- 1/2 Inch NPT Stainless Steel Union/Nipple
- Extension E Length: 4 Inches
- 316 L Stainless Steel Screw Cover Head - NEMA 4X Rated

CATALOG #: R5T185L483-S4C0308-SC-8PU491

		FOR: PYROMATION	
		TITLE: SPRING LOADED SENSOR ASSEMBLY	
		SIZE: B	DWG. NO. & SHEET NO: 10001038281
TOLERANCES		REV.	
FRACTION DIM =		DRAWN BY: GP03	DATE: 10/25/2023
DECIMAL DIM .XX =			
DECIMAL DIM .XXX =			
ANGULAR DIM =			
This document is PROPRIETARY to Pyromation			