


- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance Grade B
- Temperature Range -200 to 200 Degrees C
- 3/16 Inch Diameter 316 Stainless Steel Sheath
- 3 Wire
- Sheath Length: 2(1/2) Inches
- No Fitting or Bend
- Same Size Transition without Heat Shrink Tubing 400 Degrees F
- Leadwire - Fiberglass Insulation - Stranded Conductor - Stainless Steel Overbraid
- Extension Wire B Length: 360 Inches
- 2 Inch Split Leads 1/4 Inch Stripped



CATALOG #: R1T185L383-002(1/2)-00-18-F3B360-2

TAGGING:

STAMPING:

|  |  |   |  |
|--|--|---|--|
|  |  | FOR: PYROMATION                             |  |
|  |  | TITLE: RTD ASSEMBLY                         |  |
| TOLERANCES                                       |  | SIZE: <b>A</b>                              | DWG. NO. & SHEET NO: <b>10386000180</b> REV. |
| FRACTION DIM =                                   |  | DRAWN BY: RT01                              | DATE: 08/08/2022                             |
| DECIMAL DIM .XX =                                |  | <br><b>FORT WAYNE, INDIANA 260-484-2580</b> |  |
| DECIMAL DIM .XXX =                               |  |   |  |
| ANGULAR DIM =                                    |  |   |  |
| This document is PROPRIETARY to Pyromation, Inc. |  |   |  |