


- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance Grade B
- Temperature Range -200 to 200 Degrees C
- 1/4 Inch Diameter 316 Stainless Steel Sheath
- 3 Wire
- Sheath Length: 2 Inches
- 1/2 Inch x 1/2 Inch NPT Stainless Steel Hex Nipple
- Aluminum Screw Cover Head - NEMA 4X Rated
- Series 440 (4 to 20) mA Programmable Temperature Transmitter
- Upscale Burnout
- Range: (0 - 300)F

CATALOG #: R1T185L483-002-00-8HN31,T-440-385U-S(0-300)F

TAGGING:

STAMPING:

		FOR: PYROMATION	
		TITLE: FIXED SENSOR ASSEMBLY	
		SIZE: B	DWG. NO. & SHEET NO: 10386000125 REV.
TOLERANCES		DRAWN BY: GP01	DATE: 07/01/2021
FRACTION DIM =		 pyromation [®] <small>beyond measure</small> FORT WAYNE, INDIANA 260-484-2580	
DECIMAL DIM .XX =			
DECIMAL DIM .XXX =			
ANGULAR DIM =			
This document is PROPRIETARY to Pyromation, Inc.			