

- \* RTD ELEMENT: 100 OHM
- \* INITIAL ACCURACY: IEC CLASS A  $\pm[0.15 + 0.002 |t|]$  °C
- \* TEMPERATURE COEFFICIENT: 0.00385  $\Omega/\Omega/^\circ\text{C}$
- \* RTD ELEMENT IS HERMETICALLY SEALED INSIDE A TEFLON TUBE.


SPEC: 529 - 10 - - T3BBB-0

CUSTOMER SPECIFIED NUMBER OF LEADWIRES  
3 FOR 3 WIRE, 4 FOR 4 WIRE

CUSTOMER SPECIFIED B LENGTH

CUSTOMER SPECIFIED TERMINATION

K	UPDATED DESIGN & TEMPLATE	TR	3/26/2019
J	CHANGED ELEMENT TO AF185 FROM BF185, UPDATED TEMPLATE	CS	04/23/2011
I	UPDATED TO INVENTOR		06/26/2008
H	CHANGED DESCRIPTION AND CALLOUT OF SPEC		04/22/2003
G	NOW OFFERED AS 4-WIRE CONSTRUCTON		07/08/2002
REV	DESCRIPTION	BY	DATE

FOR: PYROMATION, INC.	
SPEC NO: 529-10	TITLE: 100 OHM RTD ASSEMBLY
SIZE: <b>A</b>	DWG. NO. & SHEET NO: <b>A069201</b>
REV: <b>K</b>	
DRAWN BY: C. STRAUB	DATE: 4/25/2011
	
This document is PROPRIETARY to Pyromation, Inc. FORT WAYNE, INDIANA 260-484-2580	