


- CIP Connected Thermowell Assembly
- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance Grade B
- Temperature Range -200 to 200 Degrees C
- 1/4 Inch Diameter 316 Stainless Steel Sheath
- 3 Wire
- Thermowell
 - 0.260 Inch Bore
 - 316 Stainless Steel
 - 1/2 Inch OD Stem
- Sanitary Cap for 1 Inch and 1 (1/2) Inch Tube Size
- 16 AMP Cap - Tri-Clamp
- S Dimension: 22 Inches
- U Dimension: 20.5 Inches
- Spring-loaded Element
- 1/2 Inch x 1/2 Inch NPT Stainless Steel Hex Nipple
- 316 L Stainless Steel Screw Cover Head - NEMA 4X Rated
- Series 440 (4 to 20) mA Programmable Temperature Transmitter
- Unconfigured

TAGGING:

STAMPING:



CATALOG #: R1T185L483-DW4152208-SL-8HN91,T-440-00

		FOR: PYROMATION	
		TITLE: DAIRY SPRINGLOADED ASSEMBLY	
		SIZE: B	DWG. NO. & SHEET NO: 10001010506
		REV.	
TOLERANCES		DRAWN BY: FD03	
DATE: 05/14/2020			
FRACTION DIM = DECIMAL DIM .XX = DECIMAL DIM .XXX = ANGULAR DIM =			
This document is PROPRIETARY to Pyromation, Inc.			