


- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance (1/5) Class B
- Temperature Range -30 to 150 Degrees C
- 1/4 Inch Diameter 316 Stainless Steel Sheath
- 4 Wire
- Sheath Length: 12 Inches
- No Fitting or Bend
- Extension Leadwire Transition with Relief Spring 400 Degrees F
- Leadwire - Fluoropolymer Insulation - Stranded Conductor - Flexible Armor
- Extension Wire B Length: 180 Inches
- Extension Wire C Length: 8 Inches
- 2 Inch Split Leads 1/4 Inch Stripped

TAGGING:

STAMPING:



CATALOG #: R5T185L484-012-00-15-T3A180-008-2

FOR:		PYROMATION	
TITLE:		RTD ASSEMBLY	
SIZE:	DWG. NO. & SHEET NO:	REV.	
A	10386000119		
DRAWN BY:		DATE:	
RT01		06/09/2021	
TOLERANCES			
FRACTION DIM = DECIMAL DIM .XX = DECIMAL DIM .XXX = ANGULAR DIM =		FORT WAYNE, INDIANA 260-484-2580	
This document is PROPRIETARY to Pyromation, Inc.			