



- Single Element RTD
- 100 ohm Platinum
- Temperature Coefficient 0.00385 ohms per Degree C
- Tolerance (1/5) Class B
- Temperature Range -30 to 150 Degrees C
- 1/4 Inch Diameter 316 Stainless Steel Sheath
- 4 Wire
- Sheath Length: 12 Inches
- No Fitting or Bend
- Extension Leadwire Transition with Relief Spring 400 Degrees F
- Leadwire - Fluoropolymer Insulation - Stranded Conductor - Flexible Armor
- Extension Wire B Length: 240 Inches
- 2 Inch Split Leads 1/4 Inch Stripped

TAGGING:

STAMPING:



CATALOG #: R5T185L484-012-00-15-T3A240-2

		FOR: PYROMATION	
		TITLE: RTD ASSEMBLY	
TOLERANCES		SIZE: A	DWG. NO. & SHEET NO: 10001013821 REV.
FRACTION DIM =		DRAWN BY: RT01	DATE: 10/16/2020
DECIMAL DIM .XX =		 pyromation [®] beyond measure FORT WAYNE, INDIANA 260-484-2580	
DECIMAL DIM .XXX =			
ANGULAR DIM =			
This document is PROPRIETARY to Pyromation, Inc.			