

14-Pin Cordsets

- For *picofast*® Junction Boxes and multi-conductor applications
- IEC IP67 Protection



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>BKM ..</p>	<p>BKM 14-002-* BKWM 14-002-*</p>	<p>BSM 14-002-* BSWM 14-002-*</p>	<p>TPU Black, 14x22 AWG, 90°C, 30 VAC/VDC, 3 A, 7.6 mm OD, Cable #RF51002-*M†, 14-wire DC applications <i>flexlife</i>®</p>	<p>Female</p> <p>Male</p>
<p>BKWM ..</p>	<p>BKM 14-000-*/S101 BKWM 14-000-*/S101</p>	<p>BSM 14-000-*/S101 BSWM 14-000-*/S101</p>	<p>TPE Black, 14x22 AWG, 105°C, 30 VAC/VDC, 3 A, 7.6 mm OD, Cable #RF51000-*M†, 14-wire DC applications, <i>flexlife</i>-20, high flex - over 20 million cycles</p>	
<p>BSM ..</p>	<p>BKM 14-998-* BKWM 14-998-*</p>	<p>BSM 14-998-* BSWM 14-998-*</p>	<p>PVC Black, 14x22 AWG, 105°C, 30 VAC/VDC, 3 A, 7.6 mm OD, Cable #RF50998-*M†, 14-wire DC applications, <i>flexlife</i></p>	
<p>BSWM ..</p>	<p>BKM 14-755-* BKWM 14-755-*</p>	<p>BSM 14-755-* BSWM 14-755-*</p>	<p>PVC Black, 12x24 AWG, 105°C, 30 VAC/VDC, 3 A, 7.0 mm OD, Cable #RF50755-*M†, 12-wire DC applications, <i>flexlife</i></p>	

* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass.. "BKM.."; "BKMK.." indicates nylon and "BKMV.." indicates stainless steel.

† See Section N for *reelfast*® cable information.